

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>The 3-12W Round Recessed Panels Die cast

10112FA/W/W



12W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms.

Supplied with 250mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Related items



89016UT

Physical Specification

Item Group

06 Downlights Fixed LED

Family

The 3-12W Round Recessed Panels Die cast



Order Code	10112FA/W/W	Pobrano z mamadecor.pl
Colour	White	
Material	Die Cast	
Diffuser Material	Acrylic	
Shape	Circular	
Height	22mm	
Diameter	173mm	
Cutout Hole Diameter	155mm	
Recessed Ceiling	Yes	
Depth Required	50mm	
Indoor	Yes	
Adjustable	No	
Electrical Characteristics		
0.5.5	Estamal la chida d	
Gear	External-Included	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	12W	
IP Rating	IP40	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	320mA	
Voltage	42V	

Safety Class	Pobrano z mamadecor.pl
Power(Watts)	10,5W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	60
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6,75-10,5W
Power Factor	0,9
Constant Current	Yes
250mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Lifud
Ilumination Data	
Colour Tomporatura	2000К
Colour Temperature	3000K
Lumen Output	720lm
Light Efficiency	60lm/W
CRI	80
Beam Angle	120°



Packing Info	
Box Length	23,5cm
Box Width	3,1cm
Box Height	18cm
Box Weight	0,410Kg
Pcs/Carton	30
Barcode	5291889044123
HS Code	9405109890

Certification & Warranty	
Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes

switch to one light!

