

## **Product Datasheet**

www.1-light.eu

06 Downlights Fixed LED>The IP54 Bathroom Downlights

## 10118B/W/W



18W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



170mm



45mm

Gallery







## **Physical Specification**

Item Group	
Family	
Order Code	
Colour	
Material	
Diffuser Material	
Shape	

06 Downlights Fixed LED

The IP54 Bathroom Downlights

10118B/W/W

White

Die Cast

Plastic

Circular

Height	45mm Pobrano z mamadecor.pl
Diameter	170mm
Cutout Hole Diameter	140mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	18W
IP Rating	IP54
Light Source	LED built in
Dimmable	No No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	34V
Safety Class	
Power(Watts)	17W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835	Pobrano z mamadecor.pl
LED Brand	Epistar	
F Mark	F	
Gear		
Gear Type	Led Driver	
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	13,5-20W	
Power Factor	0,9	
Constant Current	Yes	
500mA	27-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Ambient Temp	45°C	
Operating Temp	80°C	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	0	
Protection	Short Circuit and Overload	
lumination Data		
Colour Tomporaturo	3000K	
Colour Temperature	3000K	
Light Efficiency	1300lm 	
Light Efficiency	72,22lm/W	
CRI	90°	
Beam Angle  Illumination Diagram		

9405409900

## Certification & Warranty

**HS** Code

Packing Info

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes



