# **Product Datasheet**

www.1-light.eu

### 06 Downlights Fixed LED>The Dark Light Project Range

## 10125TD/W/C



25W LED recessed downlight, IP54. Suitable for Indoor/Outdoor installation.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.













#### Downloads









#### Dimensions



#### **Physical Specification**

Item Group	06 Downlights Fixed LED
Family	The Dark Light Project Range
Order Code	10125TD/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	235mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	140mm
Indoor	Yes

Outdoor	Yes	Pobrano z mamadecor.pl
Adjustable	No	
lectrical Characteristics		
iectrical Characteristics		
Gear	External-Included	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	25W	
IP Rating	IP54	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	600mA	
Voltage	39V	
Safety Class	<u> </u>	
Power(Watts)	23,4W	
IP Rating	IP54	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Epistar	
F Mark	F	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	18-24W	
Power Factor	0,9	
Constant Current	Yes	
600mA	30-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	ONE	
Ilumination Data		
Colour Temperature	4000K	
Lumen Output	2400lm	
Light Efficiency	95lm/W	
CRI	80	
Beam Angle	60°	
Illumination Diagram		
Dark Light	Yes	
Packing Info		
		<del></del>
Box Length	25cm	
Box Width	25cm	
Box Height	10,8cm	
Pcs/Carton	12	
Barcode	5291889069690	
HS Code	9405409900	

Warranty	2 Years
Weee Directive	Yes



