

06 Downlights Fixed LED&gt;Architectural Downlights Die cast

10128/G/W



28W LED architectural downlight, IP20.

Complete with LED driver.


Complies with standard EN60598-1 and any other specific standards.




## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

06 Downlights Fixed LED

Family

Architectural Downlights Die cast

Order Code

10128/G/W

Colour

Grey

Material

Die Cast

Diffuser Material



Acrylic

Shape

Circular

Height	85mm
Diameter	195mm
Cutout Hole Diameter	169mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes

60 Hz	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	One Light

#### Illumination Data

Colour Temperature	3000K
Lumen Output	1150lm
Light Efficiency	41lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

#### Packing Info

Box Length	25cm
Box Width	21,5cm
Box Height	11,5cm
Pcs/Carton	10
Barcode	5291889027393
HS Code	9405409900

#### Certification & Warranty

Warranty

2 Years

Pobrano z [mamadecor.pl](http://mamadecor.pl)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

