

06 Downlights Fixed LED>Dark Light Pro Range Aluminium

10130ED/W/BS/W



30W COB LED recessed downlight, for general lighting applications.

Complete with 750mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	06 Downlights Fixed LED
Family	Dark Light Pro Range Aluminium
Order Code	10130ED/W/BS/W
Colour	White-Brass
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	170mm
Cutout Hole Diameter	145mm
Recessed Ceiling	Yes
Depth Required	130mm
Indoor	Yes

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

30W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

750mA

Voltage

34,5V

Safety Class



Power(Watts)

29,3W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

LED Number

1


F Mark




Gear

Gear Type

Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	19-31,5W
Power Factor	0,9
Constant Current	Yes
750mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	LIFUD

Illumination Data

Colour Temperature	3000K
Lumen Output	2100lm
Light Efficiency	70lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	17,5cm
Box Width	12cm
Box Height	18cm
Pcs/Carton	20
Barcode	5291889058694
HS Code	9405409900

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

