

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>The Budget Downlight Range Aluminium

10124T/W/C



24W SMD LED recessed downlight, budget range, IP20.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.



55mm

Downloads









Dimensions



Gallery





Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Budget Downlight Range Aluminium
Order Code	10124T/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	55mm

Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	36V
Safety Class	
Power(Watts)	21,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

235mm

Diameter

Pobrano z mamadecor.pl

Gear	LED Number	Pobrano z mamadecor.pl
Gear Type	F Mark	F
Gear Type		
Toput Voltage	Gear	
Foot	Gear Type	Led Driver
Power(Wates)	Input Voltage	220-240V
Power(Watts) 14,5-23,2W Power Factor 0,95 Constant Current Yes 800mA 25-42V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Cable Brand Kegu Illumination Data 4000K Lumen Output 1800im Lught Efficiency 75Im/W CRI 80 Beam Angle 120° Illumination Diagram Illumination Diagram	50 Hz	Yes
Power Factor 0,95	60 Hz	Yes
Constant Current Facting FRating Fra	Power(Watts)	14,5-23,2W
Box Length 25-42V	Power Factor	0,95
IP Rating Safety Class Dimmable No Housing Material Plastic Output Terminal Cable Brand Kegu Illumination Data Colour Temperature Lumen Output Light Efficiency Tolium Angle Beam Angle Illumination Diagram Packing Info Exchange 120° Box Length 24,5cm	Constant Current	Yes
Safety Class Dimmable No Housing Material Output Terminal Brand Kegu Cable Kegu Colour Temperature Lumen Output Light Efficiency 75Im/W CRI Beam Angle Illumination Diagram Packing Info Psychology Info Example 24,5cm	600mA	25-42V
Dimmable Housing Material Output Terminal Brand Kegu Cable	IP Rating	IP20
Housing Material Output Terminal Cable Brand Kegu Illumination Data Colour Temperature 4000K Lumen Output 1800Im Light Efficiency 75Im/W CRI 80 Beam Angle 1120° Illumination Diagram Packing Info Box Length 24,5cm	Safety Class	
Output Terminal Brand Kegu Illumination Data Colour Temperature 4000K Lumen Output 1800lm Light Efficiency 75lm/W CRI 80 Beam Angle 120° Illumination Diagram Packing Info Box Length 24,5cm	Dimmable	No
Brand Kegu	Housing Material	Plastic
Illumination Data Colour Temperature 4000K Lumen Output 1800lm Light Efficiency 75lm/W CRI 80 Beam Angle 120° Illumination Diagram Packing Info Box Length 24,5cm	Output Terminal	Cable
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length 4000K 4000K 1800Im 1800Im 1800 120° 75Im/W 120° 120° 24,5cm	Brand	Kegu
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length 4000K 4000K 1800Im 1800Im 1800 120° 75Im/W 120° 120° 24,5cm		
Lumen Output1800lmLight Efficiency75lm/WCRI80Beam Angle120°Illumination DiagramThe company of the	Illumination Data	
Lumen Output1800lmLight Efficiency75lm/WCRI80Beam Angle120°Illumination DiagramThe company of the		
Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length 24,5cm		
CRI Beam Angle Illumination Diagram Packing Info Box Length 80 120° 24,5cm		
Beam Angle Illumination Diagram Packing Info Box Length 24,5cm		
Packing Info Box Length 24,5cm		80
Packing Info Box Length 24,5cm	Beam Angle	
Box Length 24,5cm	Illumination Diagram	
Box Length 24,5cm		
	Packing Info	
	Box Length	24,5cm

Box Height	6cm Pobrano z mamadecor.pl
Box Weight	0,64kg
Pcs/Carton	20
Barcode	5291889045823
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



