

## **Product Datasheet**

www.1-light.eu

06 Downlights Fixed LED>The Semi Dark Light COB Pro Range

### 10130CD/W/C



30W COB LED semi dark light recessed downlight, IP20.

Complete with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



230mm



90mm

Gallery





#### Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Semi Dark Light COB Pro Range
Order Code	10130CD/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	90mm

Cutout Hole Diameter	215mm
Recessed Ceiling	Yes
Depth Required	100mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	36V
Safety Class	
Power(Watts)	25,2W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

230mm

Diameter


Pobrano z mamadecor.pl



Led Driver
Yes
Power(Watts)
Power(Watts)         17,5-29,4W           Power Factor         0,95           Constant Current         Yes           700mA         25-42V           IP Rating         IP20           Safety Class         □           Dimmable         No           Ambient Temp         50°C           Operating Temp         85°C           Housing Material         Plastic           Output Terminal         Cable           Brand         Kegu           Illumination Data         Colour Temperature         4000K           Lumen Output         2400lm
Power Factor         0,95           Constant Current         Yes           700mA         25-42V           IP Rating         IP20           Safety Class         IIII           Dimmable         No           Ambient Temp         50°C           Operating Temp         85°C           Housing Material         Plastic           Output Terminal         Cable           Brand         Kegu           Illumination Data         Colour Temperature         4000K           Lumen Output         2400Im
Constant Current         Yes           700mA         25-42V           IP Rating         IP20           Safety Class
ToomA   25-42V     IP Rating   IP 20     Safety Class
IP Rating  Safety Class  Dimmable  Ambient Temp  Operating Temp  Housing Material  Output Terminal  Brand  Colour Temperature  Lumen Output  IIIumination Data
Safety Class  Dimmable  No  Ambient Temp  50°C  Operating Temp  85°C  Housing Material  Output Terminal  Cable  Brand  Kegu   Colour Temperature  4000K  Lumen Output  2400Im
Dimmable Ambient Temp 50°C Operating Temp 85°C Housing Material Plastic Output Terminal Cable Brand Kegu  Illumination Data  Colour Temperature 4000K Lumen Output 2400lm
Ambient Temp 50°C  Operating Temp 85°C  Housing Material Plastic  Output Terminal Cable  Brand Kegu  Illumination Data  Colour Temperature 4000K  Lumen Output 2400lm
Operating Temp Housing Material Output Terminal Brand  Cable  Kegu  Clour Temperature  Lumen Output  85°C  Plastic  Regu  2able  4000K  2400Im
Housing Material  Output Terminal  Brand  Kegu  Colour Temperature  Lumen Output  Plastic  Cable  Kegu  4000K  2400Im
Output Terminal     Cable       Brand     Kegu       Illumination Data       Colour Temperature     4000K       Lumen Output     2400lm
Regu
Colour Temperature
Colour Temperature 4000K  Lumen Output 2400lm
Colour Temperature 4000K  Lumen Output 2400lm
Lumen Output 2400lm
Lumen Output 2400lm
CRI 80
Beam Angle 180°
Illumination Diagram
Davids white
Packing Info
Box Length 24cm

Box Width	Pobrano z mamadecor.pl
Box Height	9,5cm
Box Weight	1,08kg
Pcs/Carton	6
Barcode	5291889042181
HS Code	9405409900

#### Energy Label



#### Certification & Warranty

Warranty 2 Years
Weee Directive Yes

# switch to one light!

