

04 Recessed Spots Adjustable LED&gt;The COB Recessed Cylinders

11107C/W/W



7W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery



## Must be ordered separately



89015A



89015AT


## Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Recessed Cylinders
Order Code	11107C/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	85mm
Diameter	90mm
Cutout Hole Diameter	83mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions


## Electrical Characteristics

## Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	10V
Safety Class	III
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in

LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

#### Illumination Data

Colour Temperature	3000K
Lumen Output	550lm
Light Efficiency	78,57lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

#### Packing Info

Box Length	10cm
Box Width	10cm
Box Height	10cm
Pcs/Carton	36
Barcode	5291889049241
HS Code	9405409900

#### Certification & Warranty

Warranty

5 Years

Pobrano z [mamadecor.pl](http://mamadecor.pl)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

