

New 2023 Edition 2>Downlights Adjustable LED

11115G/B/W



15W COB LED zoomable 15°-45° adjustable downlight with removable honeycomb.

Supplied with 350mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

New 2023 Edition 2

Family

Downlights Adjustable LED

Order Code

11115G/B/W

Colour

Black

Material

Aluminium

Shape



Circular

Height


47mm

Diameter	105mm
Cutout Hole Diameter	98mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	41V
Safety Class	
Power(Watts)	14,35W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

9,45-14,7W

Power Factor

0,92

Constant Current

Yes

350mA

27-42V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Cable

Brand

KGP

Protection

Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature

3000K

Lumen Output

1500lm

Light Efficiency

100lm/W

CRI

90

Beam Angle

15°-45°

Illumination Diagram



Packing Info

Pcs/Carton

27

Barcode

5291889076452

Certification & Warranty

Warranty

5 years

switch to
one light!

one
LIGHT

