

07 Downlights Adjustable LED>The COB Pop Out Range Aluminium

11125R/W/C



25W LED adjustable COB Pop Out Range, IP20.

Requires 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions




Gallery



Must be ordered separately



89030A



89030AT

Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The COB Pop Out Range Aluminium
Order Code	11125R/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	104mm
Diameter	170mm
Cutout Hole Diameter	160mm
Recessed Ceiling	Yes
Depth Required	85mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	700mA
Safety Class	III
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
LED Type	COB

LED Brand

Bridgelux

Pobrano z mamadecor.pl

Cable Length

40cm

F Mark



Illumination Data

Colour Temperature

4000K

Lumen Output

2200lm

Light Efficiency

88lm/W

CRI

80

Beam Angle

40°

Illumination Diagram



Packing Info

Box Length

22cm

Box Width

22cm

Box Height

16cm

Box Weight

1,75Kg

Pcs/Carton

8

Barcode

5291889046974

HS Code

9405409900

Certification & Warranty

Warranty

3 Years

switch to
one light!

one
LIGHT

