

07 Downlights Adjustable LED>The COB Pop Out Range Aluminium

11125R/W/W



25W LED adjustable COB Pop Out Range, IP20.

Requires 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions




Gallery



Must be ordered separately



89030A



89030AT

Physical Specification

| | |
|----------------------|---------------------------------|
| Item Group | 07 Downlights Adjustable LED |
| Family | The COB Pop Out Range Aluminium |
| Order Code | 11125R/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Circular |
| Height | 104mm |
| Diameter | 170mm |
| Cutout Hole Diameter | 160mm |
| Recessed Ceiling | Yes |
| Depth Required | 85mm |
| Indoor | Yes |
| Adjustable | 2 Directions |

Electrical Characteristics

| | |
|---------------|------------------|
| Fitting | |
| Input Type | Constant Current |
| Input Current | 700mA |
| Safety Class | III |
| Power(Watts) | 25W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |

LED Brand

Bridgelux

Pobrano z mamadecor.pl

Cable Length

40cm

F Mark



Illumination Data

Colour Temperature

3000K

Lumen Output

2070lm

Light Efficiency

82,8lm/W

CRI

80

Beam Angle

40°

Illumination Diagram



Packing Info

Box Length

22cm

Box Width

22cm

Box Height

16cm

Box Weight

1,75Kg

Pcs/Carton

8

Barcode

5291889046981

HS Code

9405409900

Certification & Warranty

Warranty

3 Years

switch to
one light!

one
LIGHT

