

07 Downlights Adjustable LED>The COB Recessed Range Die cast

11125RA/W/C



25W COB LED recessed adjustable spot, for general lighting applications.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

07 Downlights Adjustable LED

Family

The COB Recessed Range Die cast

Order Code

11125RA/W/C

Colour

White

Material

Die Cast

Shape



Circular

Height

125mm

Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	40V
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

18-30W

Power Factor

0,9

Constant Current

Yes

700mA

25.5-43V

IP Rating

IP20

Safety Class



Dimmable

No

Ambient Temp

50°C

Operating Temp

80°C

Housing Material

Plastic

Brand

Eaglerise

Protection

Short circuit Protection

Illumination Data

Colour Temperature

4000K

Lumen Output

1900lm

Light Efficiency

76lm/W

CRI

80

Beam Angle

36°

Illumination Diagram



Dark Light

Yes

Packing Info

Box Length	20,5cm
Box Width	15cm
Box Height	15cm
Box Weight	1Kg
Pcs/Carton	12
Barcode	5291889047766
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

