

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>The IP54 Bathroom Downlights

10107B/W/W



7W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED 180mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



80mm



45mm

Gallery







Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Diffuser Material	
Shape	

06 Downlights Fixed LED

The IP54 Bathroom Downlights

10107B/W/W

White

Die Cast

Plastic

Circular

Height	45mm Pobrano z mamadecor.pl
Diameter	80mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Coor	External la dude d
Gear	External-Included
Fitting + Driver	
	220.240V
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	7\\\
Power(Watts)	7W IP54
IP Rating Light Source	LED built in
Dimmable	No No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	180mA
Voltage	35V
Safety Class	
Power(Watts)	6,3W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835	Pobrano z mamadecor.pl
LED Brand	Epistar	
LED Number	14	
F Mark	F	
Gear		
Gear Type	Led Driver	
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	5,4-7,2W	
Power Factor	0,9	
Constant Current	Yes	
Output	180mA	
Voltage Range	30-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Ambient Temp	45°C	
Operating Temp	70°C	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	0	
Protection	Short Circuit and Overload	
llumination Data		
Colour Temperature	3000K	
Light Efficiency	500lm	
Light Efficiency	71,42lm/W	
CRI	80	
Beam Angle	90°	



Packing Info	
Box Length	10cm
Box Width	10cm
Box Height	9cm
Box Weight	0.228kg
Pcs/Carton	50
Barcode	5291889043188
HS Code	9405413990

Certification & Warranty	
Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes



