

Product Datasheet

www.1-light.eu

02 Recessed Spots Fixed LED>The Fire Rated IP65 Range

10107DF/W



7W COB LED Fire Rated 90 minutes recessed Spot, IP65.

Supplied with Triac dimmable LED driver.

Complete with white ring.

Complies with standard EN60598-1 and any other specific standards.















Downloads










Dimensions



Gallery





Related items





050178/B

050178/C

Physical Specification

Item Group

02 Recessed Spots Fixed LED

Family

The Fire Rated IP65 Range

Order Code	10107DF/W	Pobrano z mamadecor.pl
Colour	White	
Material	Metal	
Shape	Circular	
Height	65mm	
Diameter	78mm	
Cutout Hole Diameter	65mm	
Recessed Ceiling	Yes	
Depth Required	80mm	
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	
Electrical Characteristics		
Gear	Built In	
End and But and		
Fitting + Driver		
Fitting + Driver Input Voltage	220-240V	
	220-240V Yes	
Input Voltage		
Input Voltage 50 Hz	Yes	
Input Voltage 50 Hz 60 Hz	Yes	
Input Voltage 50 Hz 60 Hz Safety Class	Yes	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts)	Yes Yes 7W	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating	Yes Yes 7W IP65	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source	Yes Yes 7W IP65 LED built in	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	Yes Yes 7W IP65 LED built in Yes	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type	Yes Yes 7W IP65 LED built in Yes Triac	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type	Yes Yes 7W IP65 LED built in Yes Triac	
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type F Mark	Yes Yes 7W IP65 LED built in Yes Triac	

IP Rating	Pobrano z mamadecor.pl
Light Source	LED built in
LED Type	SMD
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Safety Class	
Output Terminal	Connector
Illumination Data	
	3000K
Colour Temperature	3000K 500lm
Colour Temperature Lumen Output	500lm
Colour Temperature	
Colour Temperature Lumen Output Light Efficiency	500lm 71,42lm/W
Colour Temperature Lumen Output Light Efficiency CRI	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/VV 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Weight	500lm 71,42lm/W 80 60° 0.283kg

Certification & Warranty

switch to one light!

