## **Product Datasheet**

www.1-light.eu

02 Recessed Spots Fixed LED>The Fire Rated IP65 Range

### 10107DFV/W



7W COB LED Fire Rated 90 minutes recessed Spot, IP65 with variable CCT, 2700K-3000K-4000K.

Supplied with Triac dimmable LED driver.

Complete with white ring.

Complies with standard EN60598-1 and any other specific standards.













#### Downloads










#### Dimensions



#### Gallery







#### Related items





050178/B

050178/C

#### **Physical Specification**

Item Group

02 Recessed Spots Fixed LED

Family	The Fire Rated IP65 Range Pobrar	no z mamadecor.pl
Order Code	10107DFV/W	
Colour	White	
Material	Metal	
Shape	Circular	
Height	65mm	
Diameter	78mm	
Cutout Hole Diameter	65mm	
Recessed Ceiling	Yes	
Depth Required	80mm	
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	
Electrical Characteristics		
Gear	Built In	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	7W	
IP Rating	IP65	
Light Source	LED built in	
Dimmable	Yes	
Dimmer type	Triac	
F Mark	F	
Fitting		
Input Type	Constant Current	

Power(Watts)	7W Pobrano z mamadecor.pl
IP Rating	IP65
Light Source	LED built in
LED Type	SMD
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Safety Class	
Output Terminal	Connector
Illumination Data	
	2700K 2000K 4000K
Colour Temperature	2700K-3000K-4000K
Colour Temperature  Lumen Output	510lm
Colour Temperature  Lumen Output  Light Efficiency	510lm 72,86lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	510lm 72,86lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	510lm 72,86lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	510lm 72,86lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	510lm 72,86lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	510lm 72,86lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	510lm 72,86lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	510lm  72,86lm/W  80  60°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Weight	510lm  72,86lm/W  80  60°   0.291kg
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Weight  Pcs/Carton	510lm  72,86lm/W  80  60°  0.291kg  36

# switch to one light!

