

New 2023 Edition 2>Wall & Ceiling LED

12112T/B/W



12W COB LED adjustable ceiling light.

Complete with black and brass reflectors.

Supplied with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

New 2023 Edition 2

Family

Wall & Ceiling LED

Order Code

12112T/B/W

Colour

Black

Material

Aluminium

Shape

Circular

Height

95mm

| | |
|------------------|--------------|
| Diameter | 80mm |
| Recessed Ceiling | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |


Electrical Characteristics

| | |
|------|----------|
| Gear | Built In |
|------|----------|


Fitting + Driver

| | |
|---------------|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |


Fitting

| | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 19V |
| Safety Class |  |
| Power(Watts) | 9,5W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Bridgelux |
| LED Number | 1 |

Gear

| | |
|------------------|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 6,5-9,5W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 500mA | 13-19V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | KEGU |
| Protection | Short Circuit Protection,Overload Protection,No-load Protection |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 1080lm |
| Light Efficiency | 90lm/W |
| CRI | 90 |
| Beam Angle | 36° |
| Illumination Diagram |  |
| Dark Light | Yes |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 20 |
| Barcode | 5291889076513 |
| HS Code | 9405413990 |

Warranty

5 years

switch to
one light!

one
LIGHT

