One LIGHT

Product Datasheet

www.1-light.eu

New 2023 Edition 2>Wall & Ceiling LED

12115F/W/W

15W COB LED cylinder.

Complete with 350mA driver.

Interchangeable reflector rings can be ordered separately.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI DARK LIGHT CE

Downloads

IES | 📷 | CE

Dimensions

90mm
80mm

Accessories

| 050300A/BS | 050300A/W | 050300AH/B | 0750A/15 | 0750A/24 |

Physical Specification

Item Group	New 2023 Edition 2
Family	Wall & Ceiling LED
Order Code	12115F/W/W
Colour	White
Material	Die Cast
Shape	Circular

One LIGHT

Height	80mm
Diameter	90mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	38V
Power(Watts)	13,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10,5-14,7W
Power Factor	0,9
Constant Current	Yes
350mA	30-42V
IP Rating	IP20
Safety Class	▢
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU

Illumination Data

Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	120lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.440kg
Pcs/Carton	20
Barcode	5291889076568
HS Code	9405413990

one
LIGHT

Warranty	5 years

**switch to
one light!**

one
LIGHT