www.1-light.eu

New 2023 Edition 2>Wall & Ceiling LED

 \mathbf{e}

12120F/W/W



20W COB LED cylinder.

Product Datasheet

Complete with 450mA driver.


Interchangeable reflector rings can be ordered separately.

Complies with standard EN60598-1 and any other specific standards.



Downloads		
IES	$^{\circ}$	ςε

Dimensions



Accessories



050300B/BS



050300B/W



050300BH/B



0750B/15





Item Group	New 2023 Edition 2
Family	Wall & Ceiling LED
Order Code	12120F/W/W
Colour	White
Material	Die Cast
Shape	Circular



Height	100mm	Pobrano z mamadecor.pl
Diameter	100mm	
Surface Ceiling	Yes	
Indoor	Yes	
Adjustable	No	

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	450mA
Voltage	40V
Power(Watts)	18W

110	Rating	\sim
	каши	
	- County	9
	,	\sim

Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
LED Number	1

IP20

Gear



Gear Type	Led Driver Pobrano z mamadecor.pl
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	12,15-18,9W
Power Factor	0,9
Constant Current	Yes
450mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K		
2400lm		
120lm/W		
90		
38°		
Yes		

Box Weight	0.660kg
Pcs/Carton	10
Barcode	5291889076599
HS Code	9405413990



Warranty

5 years

switch to one light!





bl