

13 Wall & Ceiling LED>The SMD Cylinders Aluminium

12135L/W/W



35W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions




Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12135L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	131mm
Diameter	195mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	35W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	800mA
Voltage	42V
Power(Watts)	33,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5630
LED Brand	Samsung

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	21,6-33,6W
Power Factor	0,9

Constant Current	Yes
800mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	3000lm
Light Efficiency	85,71lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	1.100kg
Pcs/Carton	12
Barcode	5291889041023
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
----------	---------

switch to
one light!

one
LIGHT

