## **Product Datasheet**

www.1-light.eu

### 11 Office & Kitchen>Recessed LED Linear Profiles

### 38145BR/W/C



40W UGR19 Recessed linear with 48pcs LED spots, ideal for offices.

Complete with 1000mA driver , 6pcs fixing clips, 4pcs connectors & 2pcs end cups. .

Can be connected in line

Complies with standard EN60598-1 and any other specific standards.



# Downloads IES CE

Dimensions					
Ţ	1295mm	1			
			<u>5</u> 0mm		

#### Gallery



Physical Specification	
Item Group	11 Office & Kitchen
Family	Recessed LED Linear Profiles
Order Code	38145BR/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1295mm

Width	50mm	Pobrano z mamadecor.pl
Height	55mm	
Cutout Hole Width	1280mm	
Cutout Hole Length	37mm	
Recessed Ceiling	Yes	
Depth Required	80mm	
Indoor	Yes	
Adjustable	No	
Electrical Characteristics		

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Dimmable	NO .
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030

LED Brand	Osram	Pobrano z mamadecor.pl
LED Number	48	
Gear		
Gear Type	Led Driver	
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	30-42W	
Power Factor	0,9	
Constant Current	Yes	
1000mA	30-42V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Brand	AGT	
Illumination Data		
Colour Temperature	4000K	
Lumen Output	4000lm	
Light Efficiency	100lm/W	
CRI	90	
Beam Angle	34°	
Illumination Diagram		
Dark Light	Yes	
Packing Info		
Box Weight	1.833kg	
Pcs/Carton	12	
Barcode	5291889062714	

Certification & Warranty	
o o ramino and residently	
Warranty	3 Years
•	
Weee Directive	Yes

# switch to one light!

