

Product Datasheet

www.1-light.eu

13 Wall & Ceiling LED>LED Fashion Cylinders

12108C/W/W



8W COB LED Cylinder, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	LED Fashion Cylinders
Order Code	12108C/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	70mm
Diameter	70mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	8V
Power(Watts)	5,6W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1,9-6,72W
Power Factor	0,5

Pating Pating	Constant Current	Yes Pobrano z mamadecor.pl
Safety Class □ Dimmable No Housing Material Plastic Brand Kegu Illumination Data Kegu Colour Temperature 3000K Lumen Output 520lm Light Efficiency 65lm/W GRI 90 Beam Angle 38° Illumination Diagram A Packing Info 7,5cm Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0,298kg Pcs/Carton 50 Barcode 5291889059363	700mA	2,7-9,6V
No	IP Rating	IP20
Housing Material Plastic Brand Kegu Illumination Data 3000K Colour Temperature 3000K Lumen Output 520lm Light Efficiency 65lm/W CRI 90 Beam Angle 38° Illumination Diagram ✓ Packing Info 7,5cm Box Width 7,5cm Box Weight 7,5cm Box Weight 0.298kg Pes/Carton 50 Barcode 5291889059363	Safety Class	
Brand Kegu	Dimmable	No
Colour Temperature	Housing Material	Plastic
Colour Temperature 3000K Lumen Output 520Im Light Efficiency 65Im/W CRI 90 Beam Angle 38° Illumination Diagram	Brand	Kegu
Colour Temperature 3000K Lumen Output 520Im Light Efficiency 65Im/W CRI 90 Beam Angle 38° Illumination Diagram		
Lumen Output 520 lm Light Efficiency 65 lm/W CRI 90 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info ### Pac	Illumination Data	
Lumen Output 520 lm Light Efficiency 65 lm/W CRI 90 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info ### Pac		
Light Efficiency 65lm/W CRI 90 Beam Angle 38° Illumination Diagram ✓ Packing Info 7,5cm Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Colour Temperature	3000K
CRI 90 Beam Angle 38° Illumination Diagram ✓ Packing Info 7,5cm Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Lumen Output	520lm
Beam Angle 38° Illumination Diagram ✓ Packing Info 7,5cm Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Light Efficiency	65lm/W
Packing Info	CRI	90
Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Beam Angle	38°
Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Illumination Diagram	
Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363		
Box Length 7,5cm Box Width 7,5cm Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Packing Info	
Box Width7,5cmBox Height7,5cmBox Weight0.298kgPcs/Carton50Barcode5291889059363		
Box Height 7,5cm Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Box Length	7,5cm
Box Weight 0.298kg Pcs/Carton 50 Barcode 5291889059363	Box Width	7,5cm
Pcs/Carton 50 Barcode 5291889059363	Box Height	7,5cm
Barcode 5291889059363	Box Weight	0.298kg
	Pcs/Carton	50
HS Code 9405413990	Barcode	5291889059363
	HS Code	9405413990

Warranty	3 Years
Weee Directive	Yes



