

## 13 Wall & Ceiling LED>Adjustable Display Spots

## 12108LA/B/W



8W COB LED adjustable ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads





### Dimensions



### Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Adjustable Display Spots
Order Code	12108LA/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	40mm
Diameter	78mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Adjustable	2 Directions

## Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	9V
Power(Watts)	6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,5-6,3W
Power Factor	0,9

Constant Current	Yes
700mA	5-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU

#### Illumination Data

Colour Temperature	3000K
Lumen Output	600lm
Light Efficiency	75lm/W
CRI	90
Beam Angle	25°
Illumination Diagram	
Dark Light	Yes

#### Packing Info

Box Length	10,5cm
Box Width	10,5cm
Box Height	11cm
Box Weight	0.520kg
Pcs/Carton	24
Barcode	5291889058908
HS Code	9405413990

#### Certification & Warranty

switch to  
**one light!**

one  
LIGHT

