

13 Wall & Ceiling LED>Adjustable Display Spots

12208LA/B/W



2x8W COB LED adjustable ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Adjustable Display Spots
Order Code	12208LA/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	40mm
Diameter	2x78mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	9V
Power(Watts)	2x6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,5-6,3W
Power Factor	0,5

Constant Current	Yes
700mA	5-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU

Illumination Data

Colour Temperature	3000K
Lumen Output	2x600lm
Light Efficiency	75lm/W
CRI	90
Beam Angle	25°
Illumination Diagram	

Packing Info

Box Length	18,5cm
Box Width	11,5cm
Box Height	20cm
Box Weight	0.988kg
Pcs/Carton	18
Barcode	5291889058946
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

