

06 Downlights Fixed LED>The 48W Square Panels Aluminium

50148E/W/C



60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



Must be ordered separately



89048

## Accessories



050017



050108



89048T



89050L



89050TLD

## Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 48W Square Panels Aluminium
Order Code	50148E/W/C
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

## Fitting

Input Type	Constant Current
Input Current	1200mA
Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

LED Type

SMD 2835

Pobrano z mamadecor.pl

LED Brand

Epistar

LED Number

240

#### Illumination Data

Colour Temperature

4000K

Lumen Output

4300lm

Light Efficiency

89,58lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



#### Packing Info

Box Length

72cm

Box Width

65cm

Box Height

4,5cm

Box Weight

2,7Kg

Pcs/Carton

6

Barcode

5291889041948

HS Code

9405109890

#### Certification & Warranty

Warranty

2 Years

Average Lifetime

30000 hours

Pobrano z [mamadecor.pl](http://mamadecor.pl)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

