

06 Downlights Fixed LED>The 48W Square Panels Aluminium

50148E/W/W



60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89048

Accessories



050017



050108



89048T



89050L



89050TLD

Physical Specification

| | |
|--------------------|---------------------------------|
| Item Group | 06 Downlights Fixed LED |
| Family | The 48W Square Panels Aluminium |
| Order Code | 50148E/W/W |
| Colour | White |
| Material | Aluminium |
| Diffuser Material | Acrylic |
| Shape | Rectangular |
| Length | 595mm |
| Width | 595mm |
| Height | 20mm |
| Recessed T-Ceiling | Yes |
| Depth Required | 50mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

Fitting

| | |
|---------------|------------------|
| Input Type | Constant Current |
| Input Current | 1200mA |
| Safety Class | III |
| Power(Watts) | 48W |
| IP Rating | IP20 |
| Light Source | LED built in |

LED Type

SMD 2835

Pobrano z mamadecor.pl

LED Brand

Epistar

LED Number

240

Illumination Data

Colour Temperature

3000K

Lumen Output

4000lm

Light Efficiency

83,33lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



Packing Info

Box Length

72cm

Box Width

65cm

Box Height

4,5cm

Box Weight

2,7Kg

Pcs/Carton

6

Barcode

5291889041931

HS Code

9405109890

Certification & Warranty

Warranty

2 Years

Average Lifetime

30000 hours

Pobrano z mamadecor.pl

Weee Directive

Yes

switch to
one light!

one
LIGHT

