


06 Downlights Fixed LED>The 48W Square Panels Aluminium

50148F/W/C



60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with dimmable driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items



89050L



89050TLD

Physical Specification

Item Group



06 Downlights Fixed LED

Family

The 48W Square Panels Aluminium

Order Code	50148F/W/C
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	

Fitting

Input Type	Constant Current
Input Current	1200mA



Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,4-50,4W
Power Factor	0.9
Constant Current	Yes
1200mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	Yes
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	3800lm
Light Efficiency	79,167lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info

Pcs/Carton

2

Pobrano z mamadecor.pl


Barcode

5291889034889

HS Code

9405109890

Energy Label



Certification & Warranty

Warranty

2 Years

Average Lifetime

30000 hours

Weee Directive

Yes

switch to
one light!

one
LIGHT

