

## **Product Datasheet**

www.1-light.eu

11 Office & Kitchen>The Office Floor Stand Range Aluminium

36002/W/C



60W floor stand Dimmable LED lighting fitting with EU plug.

Complete with touch switch.
Supplied with 2x700mA drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



## **Physical Specification**

11 Office & Kitchen
The Office Floor Stand Range Aluminium
36002/W/C
White
Aluminium
Rectangular
325mm

Width	665mm	Pobrano z mamadecor.pl
Height	2000mm	
Surface Floor/Ground	Yes	
Indoor	Yes	
Adjustable	No	
Electrical Characteristics		
Gear	Built In	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	60W	
IP Rating	IP20	
Light Source	LED built in	
Dimmable	Yes	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	700mA	
Voltage	36V Up 33V Down	
Power(Watts)	25,2W Up 23,1W Down	
IP Rating	IP20	
Light Source	LED built in	
LED Brand	Jufei	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	2X30W	
Power Factor	0,9	
Constant Current	Yes	
700mA	25-42V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Illumination Data		
Illumination Data  Colour Temperature	4000K	
Colour Temperature	4000K 	
Colour Temperature  Lumen Output	8000lm	
Colour Temperature  Lumen Output  Light Efficiency	8000lm 133,33lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI	8000lm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	8000lm 133,33lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI	8000lm 133,33lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  UGR	8000lm 133,33lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	8000lm 133,33lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  UGR	8000lm 133,33lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  UGR	8000lm 133,33lm/W 80 17	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  UGR  Packing Info  Box Weight	8000lm  133,33lm/W  80  17  15.400kg	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  UGR  Packing Info  Box Weight  Pcs/Carton	8000lm  133,33lm/W  80  17  15.400kg	

## Certification & Warranty

## switch to one light!

