

Product Datasheet

www.1-light.eu

07 Downlights Adjustable LED>The Box Type Shop Range

51140/B/W



40W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The Box Type Shop Range
Order Code	51140/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	235mm
Width	145mm
Height	110mm
Cutout Hole Width	220mm
Cutout Hole Length	130mm
Recessed Ceiling	Yes

Depth Required	140mm	Pobrano z mamadecor.
Indoor	Yes	
Adjustable	1 Direction	
ectrical Characteristics		
Gear	External-Included	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	40W	
IP Rating	IP20	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	1050mA	
Voltage	35V	
Safety Class	<u> </u>	
Power(Watts)	37W	
IP Rating	IP20	
Light Source	LED built in	
LED Type	СОВ	
LED Brand	Sanan	
Gear		
Gear Type	Led Driver	

Input Voltage	Pobrano z mamadecor.pl
50 Hz	Yes
60 Hz	Yes
Power(Watts)	34,65-42W
Power Factor	0,9
Constant Current	Yes
1050mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Oalawa Tamanawatuwa	000014
Colour Temperature	3000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	80
Beam Angle	70°
Illumination Diagram	
Packing Info	
Dog/Corton	0
Pcs/Carton	9
Barcode	5291889061458
110.0	0.405.400000
HS Code	9405409900

Warranty	2 Years
Weee Directive	Yes



