


INSTALLATION MANUAL

61092

LED
BUILT IN



2,5W | IP65 | SMD LED | CCT Adjustable | Dimmable | Die cast

Rechargeable USB socket.
2x4400mAh lithium battery.





80
CRI

one
LIGHT

A

CHARGE

Order separately
USB adaptor
61000A
or charging
station **61000**



100% → 0%
10 hours
(100% light intensity)



MAX 6.5 HOURS
(full recharging)





B

TOUCH SWITCH & MEMORY of BRIGHTNESS

Each time the table lamp
is switched ON, the lighting
brightness remains the same
as in previous setting.

TOUCH STEPLESS DIMMER







⚠ Only works when the light is ON



C

CCT ADJUSTABLE

⚠ Only works when the light is OFF



*The charging base is IP20

Warnings:

1. Do not cover the fitting.
2. The batteries should not be opened, destroyed or incinerate.
3. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.
4. Do not crush or puncture the battery, or immerse in liquids.
5. Avoid direct sunlight.
6. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change.
7. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

www.1-light.eu