

New 2022 Edition 2>Downlights Fixed LED

## 50140BU/W/C



60x60 UGR19 recessed backlit LED panel for T-rail false ceilings. Uniform lighting, ideal for commercial applications.

Complete with 1000mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery



### Related items



050017



050108



89042L

### Physical Specification

Item Group



New 2022 Edition 2


Family

Downlights Fixed LED

Order Code	50140BU/W/C
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	595mm
Width	595mm
Height	35mm
Recessed T-Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	No


## Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	950mA
Voltage	36V
Safety Class	

Power(Watts)	34,2W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	26,6-38W
Power Factor	0,9
Constant Current	Yes
950mA	28-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Cable Length	50cm
Brand	ONE

## Illumination Data

Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
UGR	19

## Packing Info

Box Weight	2.360kg
Pcs/Carton	6
Barcode	5291889071976
HS Code	9405119090

## Certification & Warranty

Warranty	3 years
----------	---------

switch to  
**one light!**

one  
LIGHT

