www.1-light.eu

New 2022 Edition 2>Downlights Fixed LED

50140BW/W/C

60x60 backlit IP65 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 950mA driver.

Product Datasheet

Complies with standard EN60598-1 and any other specific standards.



Downloads		Dimensions	S
ES CO	ςε	I 595mn	n I 595mm 35mm
Related items			
A CONTRACTOR OF			
050017	050108	89042L	89050TLD

Physical Specification

Item Group

New 2022 Edition 2





		••	
	m		\ /
- E A			v
			y

Downlights Fixed LED

Order Code	50140BW/W/C
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	595mm



Width	595mm	Pobrano z mamadecor.pl
Height	35mm	
Recessed T-Ceiling	Yes	
Depth Required	60mm	
Indoor	Yes	
Outdoor	Yes	
Adjustable	No	

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	

Input Type	Constant Current
Input Current	950mA

Voltage	35,2V
Safety Class	
Power(Watts)	33,44W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835



LED Brand	Sanan	Pobrano z mamadecor.pl
Gear		
Gear Type	Led Driver	
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	28,5-39,9W	
Power Factor	0,9	
Constant Current	Yes	
950mA	30-42V	
IP Rating	IP65	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	Yingjiao	
Protection	No-Load, Short Circuit	

Illumination Data

Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°

Packing Info

Pcs/Carton	6
Barcode	5291889071754



Certification & Warranty

Warranty	3 Years
Average Lifetime	50000hours
Weee Directive	Yes

switch to one light!



