

06 Downlights Fixed LED>The 48W Square Panels Aluminium

50148E/W/W



60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89048

Accessories



050017



050108



89048T



89050L



89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 48W Square Panels Aluminium
Order Code	50148E/W/W
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	1200mA
Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

LED Type

SMD 2835

Pobrano z mamadecor.pl

LED Brand

Epistar

LED Number

240

Illumination Data

Colour Temperature

3000K

Lumen Output

4000lm

Light Efficiency

83,33lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



Packing Info

Box Length

72cm

Box Width

65cm

Box Height

4,5cm

Box Weight

2,7Kg

Pcs/Carton

6

Barcode

5291889041931

HS Code

9405109890

Certification & Warranty

Warranty

2 Years

Average Lifetime

30000 hours

Pobrano z mamadecor.pl

Weee Directive

Yes

switch to
one light!

one
LIGHT

