


06 Downlights Fixed LED>The Rectangular Panels Aluminium

50148RE/W/W



120x30 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately




89048

Accessories



050017



050108



89048T



89050L



89050TLD

Physical Specification


Item Group	06 Downlights Fixed LED
Family	The Rectangular Panels Aluminium
Order Code	50148RE/W/W
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	1195mm
Width	295mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Safety Class	III
Power(Watts)	48W
IP Rating	IP20

Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	240

Illumination Data

Colour Temperature	3000K
Lumen Output	3900lm
Light Efficiency	81,25lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Pcs/Carton	4
Barcode	5291889041962
HS Code	9405109890

Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes

switch to
one light!

one
LIGHT

