

## 06 Downlights Fixed LED>The 48W Square Panels Aluminium

## 50148U/W/D



UGR19 60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



Must be ordered separately



89048

### Accessories



050017



050108



89048T



89050L



89050TLD

## Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 48W Square Panels Aluminium
Order Code	50148U/W/D
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

## Fitting

Input Type	Constant Current
Input Current	1200mA
Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

LED Type

SMD 2835

Pobrano z mamadecor.pl

LED Brand

Epistar

LED Number

240

#### Illumination Data

Colour Temperature

6000K

Lumen Output

4100lm

Light Efficiency

85,41lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



UGR

19

#### Packing Info

Box Length

72cm

Box Width

65cm

Box Height

4,5cm

Box Weight

3,2Kg

Pcs/Carton

6

Barcode

5291889044581

HS Code

9405109890

#### Certification & Warranty

Warranty

2 Years

Pobrano z [mamadecor.pl](http://mamadecor.pl)

Average Lifetime

30000 hours

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

