

21 Industrial & Floodlights>The Industrial IP65 LED UFO Range Aluminium

63100N/C

100W SMD LED Industrial High Bay, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

21 Industrial & Floodlights

Family

The Industrial IP65 LED UFO Range Aluminium

Order Code

63100N/C

Colour

Black

Material

Aluminium

Shape



Circular

Height

160mm

Diameter	250mm
Surface Ceiling	Yes
Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	100W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	30cm
F Mark	

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	190V
Power(Watts)	95W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

90-130W

Power Factor

0,9

Constant Current

Yes

500mA

180-260V

IP Rating

IP65

Safety Class



Brand

Lifud

Illumination Data

Colour Temperature

4000K

Lumen Output

13000lm

Light Efficiency

130lm/W

CRI

80

Beam Angle

90°

Illumination Diagram



Packing Info

Pcs/Carton

1

Barcode

5291889067948

HS Code

9405409900

Certification & Warranty

Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

