

## **Product Datasheet**

www.1-light.eu

10 Track Spots>Adjustable LED Linear Track Light

## 65026T/B/C



40W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



## Related items





40002A/B 40003A/B

## **Physical Specification**

Item Group	10 Track Spots
Family	Adjustable LED Linear Track Light
Order Code	65026T/B/C
Colour	Black
Material	Aluminium + Plastic
Shape	Rectangular
Length	500mm

Width	60mm Pobrano z mamadecor.pl
Height	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	28-40W	
Power Factor	0,9	
Constant Current	Yes	
1000mA	28-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	BOKE	
Protection	Short Circuit Protection	
Illumination Data		
	4000K	
Colour Temperature	4000K 	
Colour Temperature  Lumen Output	4000K 3400lm 85lm/W	
Colour Temperature	3400lm	
Colour Temperature  Lumen Output  Light Efficiency	3400lm 85lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI	3400lm 85lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3400lm 85lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm 85lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3400lm 85lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm 85lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3400lm  85lm/W  80  100°	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	3400lm 85lm/W 80 100°  51,5cm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	3400lm 85lm/W 80 100° 51,5cm 9cm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	3400lm 85lm/W 80 100° 51,5cm 9cm 13cm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	3400lm  85lm/W  80  100°  51,5cm  9cm  13cm	

Warranty	2 Years
Weee Directive	Yes



