

Product Datasheet

www.1-light.eu

09 Track Lights>Cylindrical Track Spot

65608T/G/D



3x1W LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.




Downloads






Dimensions



Related items



40003A/G

Physical Specification

Item Group	09 Track Lights
Family	Cylindrical Track Spot
Order Code	65608T/G/D
Colour	Grey
Material	Die Cast
Shape	Circular
Height	170mm

Diameter	55mm	Pobrano z mamadecor.pl
Track mounted	Yes	
Indoor	Yes	
Adjustable	2 Directions	
Electrical Characteristics		
Gear	Built In	

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Safety Class	TIII>
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3W

Constant Current Yes IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Connector Illumination Data 217/Im Lumen Output 217/Im Light Efficiency 72,33lm/W Beam Angle 60° Illumination Diagram □ Packing Info □ Barcode 5291889024071 HS Code 9405409900	Power Factor	0,5 Pobrano z mamadecor.pl
Dimmable No Housing Material Plastic Connector Noutput Terminal Colour Temperature Lumen Output Light Efficiency Beam Angle Illumination Diagram Packing Info Pes/Carton Barcode Barcode 9405409900	Constant Current	Yes
Dimmable Housing Material Output Terminal Colour Temperature 6000K Lumen Output Light Efficiency Beam Angle Illumination Diagram Packing Info Pes/Carton Barcode HS Code 9405409900	IP Rating	IP20
Housing Material Output Terminal Colour Temperature Colour Temperature Elimen Output Light Efficiency Bearn Angle Illumination Diagram Packing Info Pcs/Carton Barcode 4905409900	Safety Class	
Output Terminal Connector Illumination Data 6000K Colour Temperature 6000K Lumen Output 217lm Light Efficiency 72,33lm/W Beam Angle 60° Illumination Diagram N Packing Info 30 Barcode 5291889024071 HS Code 9405409900	Dimmable	No
Colour Temperature	Housing Material	Plastic
Colour Temperature 6000K Lumen Output 217Im Light Efficiency 72,33lm/W Beam Angle 60° Illumination Diagram Illumination Diagram Packing Info Pcs/Carton Barcode 5291889024071 HS Code 9405409900	Output Terminal	Connector
Colour Temperature 6000K Lumen Output 217Im Light Efficiency 72,33lm/W Beam Angle 60° Illumination Diagram Illumination Diagram Packing Info Pcs/Carton Barcode 5291889024071 HS Code 9405409900		
Lumen Output 217Im Light Efficiency 72,33Im/W Beam Angle 60° Illumination Diagram Illumination Diagram Packing Info Pcs/Carton Barcode 5291889024071 HS Code 9405409900	Illumination Data	
Light Efficiency 72,33lm/W Beam Angle 60° Illumination Diagram	Colour Temperature	6000K
Beam Angle	Lumen Output	217lm
Packing Info 30 Barcode 5291889024071 HS Code 9405409900	Light Efficiency	72,33lm/W
Packing Info 30 Barcode 5291889024071 HS Code 9405409900	Beam Angle	60°
Pcs/Carton 30 Barcode 5291889024071 HS Code 9405409900	Illumination Diagram	
Pcs/Carton 30 Barcode 5291889024071 HS Code 9405409900		
Pcs/Carton 30 Barcode 5291889024071 HS Code 9405409900	Packing Info	
Barcode 5291889024071 HS Code 9405409900		
HS Code 9405409900	Pcs/Carton	30
	Barcode	5291889024071
Certification & Warranty	HS Code	9405409900
Certification & Warranty		
	Certification & Warranty	
Warranty 2 Years	Warranty	2 Years
Weee Directive Yes		

switch to one light!

