

Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Spot Range Aluminium

65611T/G/W



15W COB LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items



40003A/G

Physical Specification

Item Group	09 Track Lights
Family	The COB Track Spot Range Aluminium
Order Code	65611T/G/W
Colour	Grey
Material	Aluminium
Shape	Circular
Height	105mm

Diameter	72mm	Pobrano z mamadecor.pl
Track mounted	Yes	
Indoor	Yes	
Adjustable	2 Directions	
lectrical Characteristics		
Gear	Built In	
Fitting . Driver		
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	15W	
IP Rating	IP20	
Light Source	LED built in	
Dimmable	No	
Fitting		
Input Type	Constant Current	
Input Current	350mA	
Voltage	38V	
Safety Class	ŢIII>	
Power(Watts)	13,3W	
IP Rating	IP20	
Light Source	LED built in	
LED Type	СОВ	
LED Brand	Sanan	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pi
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	9,5-14,7W	
Power Factor	0,5	
Constant Current	Yes	
350mA	27-42V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Protection	Short Circuit Protection	
Illumination Data		
	3000K	
Colour Temperature	3000K	
Colour Temperature Lumen Output	1100lm	
Colour Temperature Lumen Output Light Efficiency	1100lm 73,33lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	1100lm 73,33lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI	1100lm 73,33lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	1100lm 73,33lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	1100lm 73,33lm/W 80 36° 21cm 12,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1100lm 73,33lm/W 80 36° 21cm 12,5cm 8,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1100lm 73,33lm/W 80 36° 21cm 12,5cm 8,5cm 0,7Kg	

Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes

switch to one light!

