

Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Spot Range Aluminium

65612NT/W/C



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items





40003A/W

Physical Specification

Item Group	09 Track Lights
Family	The COB Track Spot Range Aluminium
Order Code	65612NT/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	123mm

Diameter	90mm Pobrano z mamadecor.pl
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	25-30W	
Power Factor	0,9	
Constant Current	Yes	
750mA	33-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Protection	Short Circuit Protection	
Illumination Data		
	4000K	
Colour Temperature Lumen Output	4000K 2700lm	
Colour Temperature		
Colour Temperature Lumen Output	2700lm	
Colour Temperature Lumen Output Light Efficiency	2700lm 90lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	2700lm 90lm/VV 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2700lm 90lm/VV 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2700lm 90lm/VV 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2700lm 90lm/W 90 38°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	2700lm 90lm/VV 90 38°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	2700lm 90lm/VV 90 38° 25cm 10cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	2700lm 90lm/VV 90 38° 25cm 10cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	2700lm 90lm/W 90 38° 25cm 10cm 10cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	2700lm 90lm/VV 90 38° 25cm 10cm	

Warranty	3 Years
Average Lifetime	30000 hours
Weee Directive	Yes

switch to one light!

