

Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Spot Range Aluminium

65614NT/B/W



42W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/B

Physical Specification

Item Group	09 Track Lights
Family	The COB Track Spot Range Aluminium
Order Code	65614NT/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	128mm

Diameter	100mm Pobrano z mamadecor.pl
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	42W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	38V
Safety Class	⟨III⟩
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan
Gear	

Led Driver

Gear Type

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	35-42W	
Power Factor	0,9	
Constant Current	Yes	
1050mA	33-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Protection	Short Circuit Protection	
Illumination Data		
	3000K	
Colour Temperature	3000K 	
Colour Temperature Lumen Output	3780lm	
Colour Temperature		
Colour Temperature Lumen Output Light Efficiency CRI	3780lm 90lm/W	
Colour Temperature Lumen Output Light Efficiency	3780lm 90lm/W 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3780lm 90lm/W 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/W 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3780lm 90lm/W 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/W 90	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/VV 90 38°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3780lm 90lm/W 90 38°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3780lm 90lm/W 90 38° 25cm 15cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3780lm 90lm/VV 90 38° 25cm 15cm 10,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	3780lm 90lm/W 90 38° 25cm 15cm 10,5cm	

Warranty	3 Years
Weee Directive	Yes



