

Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Spot Range Aluminium

65614T/B/W



45W COB LED track spot with, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Related items







40003A/B

Physical Specification

Item Group	09 Track Lights
Family	The COB Track Spot Range Aluminium
Order Code	65614T/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	130mm

Diameter	111mm Pobrano z mamadecor.pl
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	45W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	42V
Safety Class	<u> </u>
Power(Watts)	42W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	

Led Driver

Gear Type

Input Voltage	220-240V Pobra	no z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	24-42W	
Power Factor	0,9	
Constant Current	Yes	
1000mA	27-42V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Protection	Short Circuit Protection	
Illumination Data		
	3000K	
Colour Temperature	3000K	
Colour Temperature Lumen Output	3500lm	
Colour Temperature Lumen Output Light Efficiency	3500lm 77,78lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	3500lm 77,78lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3500lm 77,78lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	3500lm 77,78lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3500lm 77,78lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3500lm 77,78lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3500lm 77,78lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3500lm 77,78lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3500lm 77,78lm/W 80 36° 27cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3500lm 77,78lm/W 80 36° 27cm 14cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3500lm 77,78lm/W 80 36° 27cm 14cm 20,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	3500lm 77,78lm/VV 80 36° 27cm 14cm 20,5cm	

Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes

switch to one light!

