

09 Track Lights>The COB Top Box Range

65619T/W/C



38W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items



0742/15



40002A/W



40003A/W

Physical Specification

Item Group


09 Track Lights

Family

The COB Top Box Range

| | |
|---------------|--------------|
| Order Code | 65619T/W/C |
| Colour | White |
| Material | Die Cast |
| Shape | Circular |
| Height | 130mm |
| Diameter | 100mm |
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |

Electrical Characteristics

| | |
|------------------|---|
| Gear | Built In |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 38W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |

| | |
|---------------|------------------|
| Fitting | |
| Input Type | Constant Current |
| Input Current | 900mA |
| Voltage | 40V |
| Power(Watts) | 36W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

27-38W

Power Factor

0,9

Constant Current

Yes

900mA

27-42V

IP Rating

IP20

Safety Class



Dimmable

No

Ambient Temp

50°C

Operating Temp

80°C

Housing Material

Plastic

Output Terminal

Connector

Brand

Tridonic

Protection

Short Circuit Protection

Illumination Data

Colour Temperature

4000K

Lumen Output

3200lm

Light Efficiency

84,21lm/W

CRI

80

Beam Angle

36°

Illumination Diagram



Packing Info

| | |
|------------|---------------|
| Box Length | 23cm |
| Box Width | 24cm |
| Box Height | 12,5cm |
| Box Weight | 1,4kg |
| Pcs/Carton | 16 |
| Barcode | 5291889050377 |
| HS Code | 9405409900 |

Certification & Warranty

| | |
|------------------|------------|
| Warranty | 3 Years |
| Average Lifetime | 30000hours |
| Weee Directive | Yes |

switch to
one light!

one
LIGHT

