

# **Product Datasheet**

www.1-light.eu

### 09 Track Lights>The COB Cylinder Range

## 65632CT/B/W



50W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



#### Related items







40003A/B

#### **Physical Specification**

Item Group	09 Track Lights
Family	The COB Cylinder Range
Order Code	65632CT/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	160mm

Diameter	130mm	Pobrano z mamadecor.pl
Track mounted	Yes	
Indoor	Yes	
Adjustable	2 Directions	
Electrical Characteristics		
Gear	Built In	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	50W	
IP Rating	IP20	
Light Source	LED built in	
Dimmable	No	
Fitting		
Input Type	Constant Current	
Input Current	1250mA	
Voltage	37V	
Safety Class	<u> </u>	
Power(Watts)	46,25W	
IP Rating	IP20	
Light Source	LED built in	
LED Type	СОВ	
LED Brand	Cree	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	24-52,5W	
Power Factor	0,9	
Constant Current	Yes	
1250mA	37-42V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Ambient Temp	-20~50°C	
Operating Temp	90°C	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Tridonic	
Protection	Short Circuit Protection	
Protection	Short Circuit Protection	
Protection  Illumination Data	Short Circuit Protection	
Illumination Data		
Illumination Data  Colour Temperature	3000K	
Illumination Data  Colour Temperature  Lumen Output	3000K 3750lm	
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency	3000K 3750lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI	3000K 3750lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 3750lm 75lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI	3000K 3750lm 75lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 3750lm 75lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 3750lm 75lm/W 80	
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000K 3750lm 75lm/W 80	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000K 3750lm 75lm/W 80 36°	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	3000K 3750lm 75lm/W 80 36°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram  Packing Info  Box Length Box Width	3000K 3750lm 75lm/W 80 36°  32,5cm 16cm	

Pcs/Carton	6	Pobrano z mamadecor.pl
Barcode	5291889047773	
HS Code	9405409900	

# Warranty 3 Years Average Lifetime 30000hours Weee Directive Yes



