

14 Plafo&gt;The LED Project Plafo Metal

62125D/W/C



25W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads






## Dimensions




## Physical Specification

|                 |                             |
|-----------------|-----------------------------|
| Item Group      | 14 Plafo                    |
| Family          | The LED Project Plafo Metal |
| Order Code      | 62125D/W/C                  |
| Colour          | White                       |
| Material        | Metal                       |
| Shape           | Circular                    |
| Height          | 106mm                       |
| Diameter        | 400mm                       |
| Surface Ceiling | Yes                         |
| Indoor          | Yes                         |
| Adjustable      | No                          |


| Gear             | External-Included   |
|------------------|---|
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |    |
| Power(Watts)     | 25W   |
| IP Rating        | IP20  |
| Light Source     | LED built in  |
| Dimmable         | No  |
| F Mark           |  |

| Fitting       |   |
|---------------|---|
| Input Type    | Constant Current  |
| Input Current | 700mA   |
| Voltage       | 40V   |
| Power(Watts)  | 28W   |
| IP Rating     | IP20  |
| Light Source  | LED built in  |
| LED Type      | SMD 2835  |
| LED Brand     | Bridgelux   |
| LED Number    | 50  |
| F Mark        |  |

| Gear          |            |
|---------------|------------|
| Gear Type     | Led Driver |
| Input Voltage | 220-240V   |
| 50 Hz         | Yes        |
| 60 Hz         | Yes        |

|                  |   |
|------------------|---|
| Power(Watts)     | 19-30W  |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 700mA            | 27-42V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Housing Material | Plastic   |
| Output Terminal  | Cable   |
| Brand            | KEGU  |

### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 4000K   |
| Lumen Output         | 2125lm  |
| Light Efficiency     | 85lm/W  |
| CRI                  | 80  |
| Beam Angle           | 120°  |
| Illumination Diagram |  |

### Packing Info

|            |               |
|------------|---------------|
| Box Weight | 2.200kg       |
| Pcs/Carton | 1             |
| Barcode    | 5291889046752 |
| HS Code    | 9405413990    |

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

