

14 Plafo>The LED Plafo Outdoor Round

67280BN/G/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|-------------------|-----------------------------|
| Item Group | 14 Plafo |
| Family | The LED Plafo Outdoor Round |
| Order Code | 67280BN/G/W |
| Colour | Grey |
| Material | Plastic |
| Diffuser Material | PC |
| Shape | Circular |
| Height | 83mm |
| Diameter | 360mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Outdoor | Yes |

Adjustable

No

Pobrano z mamadecor.pl

IK Rating

8

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

30W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

700mA

Voltage

38V

Power(Watts)

28W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

LED Number

144


F Mark




Gear

Gear Type

Led Driver

| | |
|------------------|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 18,2-30W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 700mA | 26-43,5V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | Eaglerise |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 1800lm |
| Light Efficiency | 60lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Length | 37cm |
| Box Width | 37cm |
| Box Height | 9cm |
| Box Weight | 1.700kg |
| Pcs/Carton | 5 |
| Barcode | 5291889043362 |
| HS Code | 9405114090 |

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

