## **Product Datasheet**

www.1-light.eu

## 14 Plafo>The LED Plafo Outdoor Round

## 67280BN/W/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



## **Physical Specification**

Item Group	14 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280BN/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	83mm
Diameter	360mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No	Pobrano z mamadecor.p
IK Rating	8	
atrical Charactaristics		
ctrical Characteristics		
Gear	Built In	
Fitting + Driver		
nput Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	30W	
IP Rating	IP65	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	700mA	
Voltage	38V	
Power(Watts)	28W	
IP Rating	IP65	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Epistar	
LED Number	144	
F Mark	F	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	18,2-30W	
Power Factor	0,9	
Constant Current	Yes	
700mA	26-43,5V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Eaglerise	
Ilumination Data		
Oalassa Tarasa anatsura	000014	
Colour Temperature	3000K	
Colour Temperature  Lumen Output	3000K 1800lm	
Lumen Output	1800lm	
Lumen Output Light Efficiency	1800lm 60lm/W	
Lumen Output  Light Efficiency  CRI	1800lm 60lm/W	
Lumen Output  Light Efficiency  CRI	1800lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	1800lm 60lm/W 80	
Lumen Output Light Efficiency CRI Illumination Diagram	1800lm 60lm/W	
Lumen Output  Light Efficiency  CRI  Illumination Diagram	1800lm 60lm/W 80	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	1800lm 60lm/W 80 7	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	1800lm 60lm/W 80 37cm 37cm	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1800lm 60lm/W 80 37cm 37cm 9cm	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1800lm 60lm/W 80 37cm 37cm 9cm 1.700kg	
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	1800lm 60lm/W 80 37cm 37cm 9cm 1.700kg	

Warranty	2 Years
Weee Directive	Yes



