

Product Datasheet

www.1-light.eu

10 Track Spots>Adjustable LED Linear Track Light

65026T/W/W



40W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Related items







40003A/W

Physical Specification

Item Group	10 Track Spots
Family	Adjustable LED Linear Track Light
Order Code	65026T/W/W
Colour	White
Material	Aluminium + Plastic
Shape	Rectangular
Length	500mm

Width	60mm Pobrano z mamadecor.pl
Height	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	28-40W	
Power Factor	0,9	
Constant Current	Yes	
1000mA	28-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	KEGU	
Protection	Short Circuit Protection	
Illumination Data		
	3000K	
Colour Temperature	3000K 	
Colour Temperature Lumen Output	3000K 3200lm 80lm/W	
Colour Temperature	3200lm	
Colour Temperature Lumen Output Light Efficiency	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3200lm 80lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3200lm 80lm/W 80 100°	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3200lm 80lm/W 80 100° 51,5cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3200lm 80lm/W 80 100° 51,5cm 9cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3200lm 80lm/W 80 100° 51,5cm 9cm 13cm	
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	3200lm 80lm/W 80 100° 51,5cm 9cm 13cm	

Warranty	2 Years
Weee Directive	Yes



