

Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Light Range Aluminium

65612NT/B/W



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40002A/B



40003A/B

Physical Specification

| Item Group | 09 Track Lights |
|------------|-------------------------------------|
| Family | The COB Track Light Range Aluminium |
| Order Code | 65612NT/B/W |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |
| Height | 123mm |
| | |

| Diameter | 90mm Pobrano z mamadecor.pl |
|----------------------------|-----------------------------|
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |
| | |
| Electrical Characteristics | |
| | |
| Gear | Built In |
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 30W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 750mA |
| Voltage | 38V |
| Safety Class | <u> </u> |
| Power(Watts) | 28,5W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| LED Brand | Bridgelux |
| | |
| Gear | |
| Gear Type | Led Driver |

| Input Voltage | 220-240V | Pobrano z mamadecor.pl |
|---|--------------------------|------------------------|
| 50 Hz | Yes | |
| 60 Hz | Yes | |
| Power(Watts) | 25-30W | |
| Power Factor | 0,9 | |
| Constant Current | Yes | |
| 750mA | 33-40V | |
| IP Rating | IP20 | |
| Safety Class | | |
| Dimmable | No | |
| Housing Material | Plastic | |
| Output Terminal | Connector | |
| Brand | Lifud | |
| Protection | Short Circuit Protection | |
| | | |
| Ilumination Data | | |
| Colour Tomporatura | 20001/ | |
| Colour Temperature | 3000K | |
| Light Efficiency | 2700lm | |
| Light Efficiency | 90lm/W | |
| CRI | 90 | |
| Beam Angle | 200 | |
| Illumination Diagram | 38° | |
| Illumination Diagram | 38° | |
| Illumination Diagram | 38° | |
| Illumination Diagram Packing Info | 38° | |
| | 38° | |
| Packing Info | | |
| Packing Info Box Length | 25cm | |
| Packing Info Box Length Box Width | 25cm 10cm | |
| Packing Info Box Length Box Width Box Height | 25cm 10cm | |
| Packing Info Box Length Box Width Box Height Box Weight | 25cm 10cm 10cm 1.140kg | |

| Certification & Warranty | |
|--------------------------|---------|
| Warranty | 3 years |
| Weee Directive | Yes |

switch to one light!

