

## **Product Datasheet**

www.1-light.eu

09 Track Lights>The COB Track Light Range Aluminium

### 65612NT/W/W



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



#### Related items







40002A/W



40003A/W

#### **Physical Specification**

09 Track Lights
The COB Track Light Range Aluminium
65612NT/W/W
White
Aluminium
Circular
123mm

Diameter	90mm Pobrano z mamadecor.pl
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	Pobrano z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	25-30W	
Power Factor	0,9	
Constant Current	Yes	
750mA	33-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
Protection	Short Circuit Protection	
Ilumination Data		
	3000K	
Colour Temperature	3000K 	
Colour Temperature  Lumen Output	2700lm	
Colour Temperature  Lumen Output  Light Efficiency	2700lm 90lm/W	
Colour Temperature  Lumen Output  Light Efficiency  CRI	2700lm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	2700lm 90lm/W 90	
Colour Temperature  Lumen Output  Light Efficiency  CRI	2700lm 90lm/W 90	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	2700lm 90lm/W 90	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	2700lm 90lm/W 90	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	2700lm 90lm/W 90	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	2700lm 90lm/W 90 38°	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	2700lm 90lm/VV 90 38°	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	2700lm 90lm/VV 90 38° 25cm 10cm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	2700lm 90lm/VV 90 38°  25cm 10cm	
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	2700lm 90lm/VV 90 38° 25cm 10cm 10cm 1.140kg	

Certification & Warranty	
Warranty	3 years
Weee Directive	Yes

# switch to one light!

