

20 Garden &amp; Underwater&gt;The LED Bollards Range Cone reflector

**67410/AN/C**

12W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Physical Specification

|                      |                                       |
|----------------------|---------------------------------------|
| Item Group           | 20 Garden & Underwater                |
| Family               | The LED Bollards Range Cone reflector |
| Order Code           | 67410/AN/C                            |
| Colour               | Anthracite                            |
| Material             | Die Cast                              |
| Diffuser Material    | PC                                    |
| Shape                | Circular                              |
| Height               | 800mm                                 |
| Diameter             | 120mm                                 |
| Surface Floor/Ground | Yes                                   |
| Outdoor              | Yes                                   |
| Adjustable           | No                                    |

## Electrical Characteristics

## Gear

## Built In

## Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

12W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



## Fitting

Input Type

Constant Current

Input Current

250mA

Voltage

44V

Power(Watts)

11W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Edison

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz


Yes

60 Hz

Yes

|                  |   |
|------------------|---|
| Power(Watts)     | 9-12W   |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 250mA            | 36-48V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Ambient Temp     | -20~55°C  |
| Operating Temp   | 85°C  |
| Housing Material | Plastic   |
| Output Terminal  | Connector   |
| Brand            | Eaglerise   |
| Protection       | Short Circuit   |

#### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 4000K   |
| Lumen Output         | 1000lm  |
| Light Efficiency     | 83,33lm/W   |
| CRI                  | 80  |
| Illumination Diagram |  |

#### Packing Info

|            |               |
|------------|---------------|
| Box Weight | 3,45Kg        |
| Pcs/Carton | 2             |
| Barcode    | 5291889051640 |
| HS Code    | 9405409900    |

Certification & Warranty

|                  |            |
|------------------|------------|
| Warranty         | 3 Years    |
| Average Lifetime | 50000hours |
| Weee Directive   | Yes        |

switch to  
**one light!**

one  
LIGHT

